

600⁺ 切削條件表 **P344**
Cutting Condition

Roughing Type - 3 flutes

3刃粗銑立銑刀

600 PLUS



HRC > 45

25°

a_1
 $b > a$

● Micro Grain Carbide

● WC=90 Co=10 HV30=1571 Rupture=3750N/mm² Grain Size=0.6μm



Dimension 規格					Purchase Code 採購代碼			
Diameter	Flute Length	Full Length	Shank Diameter	Flutes	MODE	Coating 塗層		
d 刃徑	l 刃長	L 全長	D 柄徑	Z 刃數	型號	ALTIBN	TISIN	ZrN-A
4	8	50	6	3	P-XTA0403	.01	.02	.03
5	13	50	6	3	P-XTA0503	.01	.02	.03
6	16	50	6	3	P-XTA0603	.01	.02	.03
7	16	60	8	3	P-XTA0703	.01	.02	.03
8	19	60	8	3	P-XTA0803	.01	.02	.03
9	25	75	10	3	P-XTA0903	.01	.02	.03
10	25	75	10	3	P-XTA1003	.01	.02	.03
11	30	75	12	3	P-XTA1103	.01	.02	.03
12	30	75	12	3	P-XTA1203	.01	.02	.03
16	35	100	16	3	P-XTA1603	.01	.02	.03
20	45	100	20	3	P-XTA2003	.01	.02	.03

- HRC > 40
- HRC > 45
- HRC > 50
- HRC > 55
- HRC > 60
- HRC > 65
-
-
-
-
-
-
-
-
-
-

Application 適用材質：

★ Perfect 最推薦 ◎ Excellent 適合 ○ Good 佳

Coating 塗層	Carbon steel, Alloy steel 炭素鋼, 合金鋼	Pre-hardened steel 預硬鋼	High-hardened 高硬度鋼				Stainless steel 不鏽鋼	Titanium alloy 鈦合金	Nickel/Inconel alloy 鎳基合金	Copper alloy 銅合金, 銅	Aluminum alloy 鋁合金
		~45HRC	~50HRC	~55HRC	~60HRC	~65HRC					
ALTIBN	◎	◎	○				○				
TISIN	○	◎	○	○							
ZrN-A	◎	◎	○				○				

Unit/單位: mm