

600⁺ 切削條件表 **P342**
Cutting Condition

Fine Pitch & Roughing Type - 3 flutes



■ 3刃粗精銑立銑刀

600
PLUSHRC
45

40°

a
b > a

● Micro Grain Carbide

● WC=90 Co=10 HV30=1571 Rupture=3750N/mm² Grain Size=0.6μm

Dimension 規格					Purchase Code 採購代碼			
Diameter	Flute Length	Full Length	Shank Diameter	Flutes	MODE	Coating 塗層		
d 刃徑	L 刃長	L 全長	D 柄徑	Z 刃數	型號	ALTBN	TISIN	ZrN-A
4	8	50	6	3	P-NTA0403	.01	.02	.03
5	13	50	6	3	P-NTA0503	.01	.02	.03
6	16	50	6	3	P-NTA0603	.01	.02	.03
7	16	60	8	3	P-NTA0703	.01	.02	.03
8	19	60	8	3	P-NTA0803	.01	.02	.03
9	25	75	10	3	P-NTA0903	.01	.02	.03
10	25	75	10	3	P-NTA1003	.01	.02	.03
11	30	75	12	3	P-NTA1103	.01	.02	.03
12	30	75	12	3	P-NTA1203	.01	.02	.03
16	35	100	16	3	P-NTA1603	.01	.02	.03
20	45	100	20	3	P-NTA2003	.01	.02	.03

Application 適用材質：

★ Perfect 最推薦

◎ Excellent 適合

○ Good 佳

Coating 塗層	Carbon steel, Alloy steel 炭素鋼, 合金鋼	Pre-hardened steel 預硬鋼	High-hardened 高硬度鋼					Stainless steel 不鏽鋼	Titanium alloy 鈦合金	Nickel/Inconel alloy 鎳基合金	Copper alloy 銅合金, 銅	Aluminum alloy 鋁合金
		~45HRC	~50HRC	~55HRC	~60HRC	~65HRC						
ALTBN	◎	◎	○				○					
TISIN	○	◎	○	○								
ZrN-A	◎	◎	○				○					

Unit/單位: mm