

切 削
條件表
Cutting Condition

P407

Ball Nose Type - Long Neck - For Copper & Aluminum - 2 flutes


■ 2刃長頸銅鋁球型立銑刀

600
Nano

25°

TB

● Micro Grain Carbide

● WC=90 Co=10 HV30=1571 Rupture=3750N/mm² Grain Size=0.6μm

MODE	Diameter	Radius	Flute Length	Efficient Length	Full Length	Shank Diameter	Neck Diameter	Flutes
型號	d 刀徑	R 值	刀長	L1 有效長	L 全長	D 柄徑	頸徑	Z 刃數
ACBL1004 TB	1	0.5	2	4	50	4	0.95	2
ACBL1006 TB	1	0.5	2	6	50	4	0.95	2
ACBL1010 TB	1	0.5	2	10	50	4	0.95	2
ACBL1012 TB	1	0.5	2	12	50	4	0.95	2
ACBL1016 TB	1	0.5	2	16	50	4	0.95	2
ACBL1506 TB	1.5	0.75	3	6	50	4	1.45	2
ACBL1510 TB	1.5	0.75	3	10	50	4	1.45	2
ACBL1512 TB	1.5	0.75	3	12	50	4	1.45	2
ACBL1516 TB	1.5	0.75	3	16	50	4	1.45	2
ACBL2008 TB	2	1.0	4	8	50	4	1.92	2
ACBL2012 TB	2	1.0	4	12	50	4	1.92	2
ACBL2014 TB	2	1.0	4	14	50	4	1.92	2
ACBL2020 TB	2	1.0	4	20	50	4	1.92	2
ACBL3012 TB	3	1.5	6	12	50	6	2.9	2
ACBL3016 TB	3	1.5	6	16	50	6	2.9	2
ACBL3020 TB	3	1.5	6	20	60	6	2.9	2
ACBL3025 TB	3	1.5	6	25	75	6	2.9	2
ACBL4010 TB	4	2	8	10	60	6	3.88	2
ACBL4012 TB	4	2	8	12	60	6	3.88	2
ACBL4016 TB	4	2	8	16	60	6	3.88	2
ACBL4020 TB	4	2	8	20	60	6	3.88	2
ACBL4025 TB	4	2	8	25	75	6	3.88	2

• Tolerance for Ball radius : $\pm 0.01\text{mm}$ R容許差

Application 適用材質：

★ Perfect 最推薦

◎ Excellent 適合

○ Good 佳

carbon steel, Alloy steel 炭素鋼, 合金鋼	Pre-hardened steel 預硬鋼	High-hardened 高硬度鋼				Stainless steel 不銹鋼	Copper alloy 銅合金, 銅	Aluminum alloy 鋁合金
	~45HRC	~50HRC	~55HRC	~60HRC	~65HRC			
							◎	◎

Unit/單位: mm